WANPIPE Multi Protocol WANPIPE Driver

DEBUGGING MANUAL

Copyright © 1995, 2003 Sangoma Technologies Inc.



By Nenad Corbic

LIMITED USE WARRANTY

WANPIPE Driver for Linux operating system Copyright © 1995-2003 Sangoma Technologies Inc.

WANPIPE drivers are distributed with the purchase of Sangoma S-series cards. The drivers are free software; you can redistribute and/or modify them under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Sangoma Technologies

Markham, Ontario, Canada

Contents

1. Introduction	4
Standards Used in This Manual	4
2. Line Debugging	5
Local Debugging	
Remote Debugging	5
3. Common Wanpipemon Statistics	
4. Wanpipe Debugging	7
Wanrouter Log File	7
Kernel Log File	
5. Contacting Sangoma Tech Support	

1. Introduction

At the heart of WANPIPE debugging is the 'wanpipemon' debugging program. It is used to display line traces, protocol statistics, hardware statistics and configuration parameters.

```
/usr/sbin/wanpipemon -g
```

When debugging an installation follow these steps:

- Physical Inspection
 - Check to see that the installation is recognized.
 - Check that the configuration process has been completed.
 - Start the WANPIPE drivers.
- 2. Connection and Condition of Line
 - Check the physical connection, the CSU/DSU.
 - · Check the datalink Protocols.
- 3. Routing and Internet Protocol
 - Try to ping the ISP server.

Standards Used in This Manual

In the samples below, the variable [if_name] represents the name of a wanpipe interface. For example wp1fr16.

To display a report on the screen:

```
/usr/sbin/wanrouter debug [if_name]
```

To send a report to a text file:

```
/usr/sbin/wanrouter debug [if_name] > debug_file.txt
```

To simplify the table below, variables with square brackets (for example [command]) represent the named command, address, interface name, etc.

Options in curly brackets (for example { -p }). Some examples contain optional parameters with named variables.

2. Line Debugging

To find out what signals are being sent over the sync line, the wanrouter operation script can retrieve common line error statistics.

Local Debugging

Table 1 - WANPIPE Monitor Commands

Command String	Description
wanpipemon -i <interface> -c <command/> { -p <pre>protocol> }</pre></interface>	The 'wanpipemon' utility is located on the same machine as the WANPIPE card. To communicate with the driver, the wanpipemon utility needs only the interface name (for example: wp1_fr16).
	/usr/sbin/wanpipemon -i wpl_fr16 -c xm

Remote Debugging

Table 2 - Commands for Remote Debugging

Command String	Description		
wanpipemon -i <remote ip=""> -u <port> -c <command/> { -p <pre>protocol> }</pre></port></remote>	The 'wanpipemon' utility is located on a network (LAN or WAN) and must use the UDP protocol to reach the WANPIPE card.		
	In this case an IP and UDP addresses must be specified, such that the packet will pass through the WANPIPE driver! Meaning a POINTOPOINT address must be used instead of the LOCAL IP address.		
	The UDP port was specified in WANPIPE configuration file. (Default=9000)		
	/usr/sbin/wanpipemon -i 201.1.1.2 -u 9000 -c xm		
#GUI interface	wanpipemon -g { -i <interface ip> -u <port> -p <protocol> }</protocol></port></interface ip>		
The GUI mode is based on ncurses libraries, thus it will work both in Terminal or Xwindows mode.			
/usr/sbin/wanpipemon -g			
Without any other arguments the GUI will offer a list of network interfaces, for local debugging, or will ask for an IP/UDP address, for remote debugging.			
Use menus to navigate through available commands.			
#Display usage for each protocol	wanpipemon -p [fr ppp chdlc x25 adsl]		
#Detailed usage for each option	wanpipemon –h		

3. Common Wanpipemon Statistics

Use these command strings to display various aspects of performance.

Table 3 - Wanpipemon Statistics

Performance Aspect	Command String	Comments
Modem Status (-c xm)	wanpipemon -i wp1fr16 -c xm	Resulting display must show DCD=HIGH and CTS=HIGH.
		If you do not get these results, there is either a cable problem or the sync line is not turned on.
Communication Error Status (-c sc)	wanpipemon -i wp1fr16 -c sc	Check for CRC and Abort errors.
		If errors appear and if they are incrementing, there is a line issue.
		Possible reasons:
		 CSU/DSU misconfiguration on local or remote side.
		- Noisy or bad line.
Line trace (-c tr)	wanpipemon -i wp1fr16 -c tr	Make sure there are both incoming and outgoing frames.
		If frames are going out and no frames are coming in:
		Frame relay: Check signaling (ANSI, LMI). Make sure ISP uses IETF or CISCO data encapsulation.
		Other protocols: Possible CRC errors in TX direction. Contact your ISP.
		If frames are both coming in and going out but protocol is still down:
		Run trace in Interpreted mode (-c ti) and make sure that the incoming protocol is the correct one you are configured for.



4. Wanpipe Debugging

Wanrouter Log File

wanrouter conflogs or cat /var/log/wanrouter

All WANPIPE configuration file syntax errors will be displayed in wanrouter log file. If the wanrouter command returns a syntax error, the description of the error will be generated in /var/log/wanrouter log file.

Kernel Log File

wanrouter messages #Display all wanpipe messages

or

tail -f /var/log/messages #Display last ten lines and any new lines

#until session ended by user.


All WANPIPE, kernel module events and errors will be displayed in syslog. The most common syslog file is /var/log/messages.



5. Contacting Sangoma Tech Support

When reporting problems to Sangoma Tech Support please dump the current system debug information into a temporary file and send it via email.

- Run wanrouter debug wplfr16 > sangoma_debug_file.txt to log results in the text file.
- 2. Wait for 2-5 minutes to gather data.
- 3. Stop the debug by pressing Enter.
- **4.** Email sangoma_debug_file.txt to Sangoma Tech Support mailto:support@sangoma.com.



The above diagram displays a Wanpipe line debugging flow chart. Each flow chart command (e.g.: Tv) is a /usr/sbin/wanpipemon command.

If the chart indicates that statistics for command xm are required, a full command would look like the following:

/usr/sbin/wanpipemon -i if_name -c xm

